



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
TRACKED AERIALS

TEUPEN TC/TL79AJ^{plus}

SPECIFICATIONS


PERFORMANCE

Max Working Height	78.7 ft (24 m)
Max Platform Height	72.1 ft (22 m)
Horizontal Outreach (220.4 lbs / 100 kg)	47.9 ft (14.6 m)
Horizontal Outreach (551.1 lbs / 250 kg)	40.3 ft (12.3 m)
Max Negative Reach	16.4 ft (5 m)
Max Up-and-Over Clearance	31.1 ft (9.5 m)
Max Platform Capacity (Aluminum)	551.1 lbs (250 kg)
Max Platform Capacity (GRP)	348.3 lbs (158 kg)
Jib, Movable	165°
Platform Rotation	180°
Max Turntable Rotation	450°
To be Jacked up on Ground Slope of	16.7° / 30 %
Track drive, height and width adjustable	0.8 ft x 1.3 ft (26 cm / 42 cm)
Gradeability, Max	16.7° / 30 %
Slope Angle, Max	16.7° / 30 %
Travel Speed, Max	1.5 mph (2.5 kph)

POWER SOURCES

Standard Power Sources	
Electric	230 V, 12.9 A, 2.2 kW
Diesel	Kubota D902 (16.1 kW / 21.9 hp)
Fuel tank capacity (Diesel Engine)	3 gal (11.5 L)

WORKING ENVELOPE



MEASUREMENTS*

Platform Height (A)	3.6 ft (1.1 m)
Platform Length (B)	4.5 ft (1.4 m)
Platform Width (C)	2.2 ft (0.7 m)
Length (D)	21.2 ft (6.4 m)
Length without platform (E)	21.2 ft (6.4 m)
Height (F)	6.5 ft (1.9 m)
Width, min. (G)	2.9 ft (0.8 m)
Max Ground Clearance (H)	1 ft (0.3 m)
Track (length x width) (I)	4.9 ft x 0.7 ft (1.5 m x 0.2 m)
Stabilizer footprint both sides wide (length) (J)	16 ft (4.9 m)
Stabilizer footprint both sides wide (width) (K)	15.4 ft (4.7 m)
Stabilizer footprint one side narrow (length) (L)	21.3 ft (6.5 m)
Stabilizer footprint one side narrow (width) (M)	9.8 ft (2.9 m)
Stabilizer footprint both sides narrow (width) (N)	12.7 ft (3.9 m)
Stabilizer footprint both front or back narrow (length) (O)	18.6 ft (5.6 m)
Stabilizer plate Ø	0.5 ft (0.1 m)

WEIGHT


Total Weight	8,278.3 lbs (3,755 kg)
Live Load in Traveling Position	98.5 psf (4.7 kN/m²)
Live Load in Working Position	35.9 psf (1.7 kN/m²)
Point Load per Outrigger Plate, Max	6,519.4 lbf (29 kN)

POWER SUPPLY

Electric Current, Max	115 V / 13 A
-----------------------	--------------

The technical data may deviate +/- 3% from the specified values.

* Weight and dimensions may vary depending on options and accessories.



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.
© 2026 Altec Inc. All Rights Reserved. Altec_TeupenCTL79AJplus_SBM_031626



NEW EQUIPMENT SALES

| 800.958.2555

| SALES@ALTEC.COM

| ALTEC.COM