



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
DIGGER DERRICK

DL SERIES

Altec B-Series derricks are a staple of the electric utility and telecom industries. B-Series includes a 43 gpm variable displacement piston pump which reduces hydraulic heat generation, fuel consumption and chassis wear. Additionally, optional radio remotes integrate directly with the control system unlike fully hydraulic derricks and are offered with HOP indication. Additional features and options like standard and low speed for unit function, optional electronic side load protection with load gauge and RotaFloat® help to provide safety and productivity at the jobsite.

FEATURES

- Multi-Lever Control Station Riding Seat
- Five Function Hydraulic Overload Protection System (HOP)
- Standard/Low Speed Selector
- Insulating Fiberglass Third Stage, Rated to 46kV and Below
- Fiberglass Boom Tip and Transferable Steel Boom Flares
- Hydraulic Side Load Protection
- 15,000 lb Worm Gear Turntable Winch with Rope Guides
- Hydraulic Tilting Pole Guides with Interlock
- 12,000 ft-lbs Digger Motor, Two Speed Mechanical Shift
- Hydraulic Auger Release
- Boom and Auger Stow Protection

Recommended equipment and additional accessories, available through Altec Supply includes, the AXIS Service Interface Kit, a platform liner, fall protection system, wheel chocks and outrigger pads.

OPTIONS

- Altec Opti-View® Riding Seat
- Altec Electronic Side Load Protection with Load Gauge
- Altec RotaFloat®
- Radio Remote Derrick Controls with HOP Indication
- Docking Station for Radio Upper Controls
- Integrated Multi-Lever Upper Controls
- Boom Tip Winch
- Corner Mount
- Behind Cab Mount
- Pole Guide Tong Protectors
- Single or Dual Platform(s)

CONFIGURATIONS

SPECIFICATIONS		DL42	DL45
	Maximum Sheave Height* (Both Booms Extended)	41.4 ft (12.6 m)	44.3 ft (13.5 m)
	Horizontal Reach from Centerline of Rotation (Both Booms Extended)	31.6 ft (9.6 m)	34.6 ft (10.5 m)
	Maximum Lift Capacity	30,000 lb (13,608 kg)	30,000 lb (13,608 kg)
	Maximum Lift Capacity (at 10 ft Radius without Options)	10,280 lb (4663 kg)	9,850 lb (4468 kg)
	Boom Articulation	-18 to 84°	-18 to 84°
	Digger Radius (min - max)	14.2 ft (4.3 m) - 21.5 ft (6.5 m)	15.7 ft (4.8 m) - 24.5 ft (7.4 m)
	Rotation (with High Capacity Worm Drive Gearbox)	Continuous	Continuous
	Travel Height, approximate	11.9 ft (3.6 m)	11.9 ft (3.6 m)
*Based on a 40 in (1016 mm) chassis frame height.			



OPTI-VIEW® CONTROL SEAT

The Altec Opti-View® Control Seat increases operator comfort and provides a full view of the work area.



SIDE LOAD GAUGE

The side load indicator gauge can give operators advanced warning of potential loading hazards.



RADIO REMOTE CONTROLS

The radio unit can be used as upper controls without running mechanical controls to the boom tip, allowing a greater boom capacity and smaller working envelope.



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2021 Altec Inc. All Rights Reserved. AIOSDL SERIES-0321-v4-r1



NEW EQUIPMENT SALES

800.958.2555

SALES@ALTEC.COM

ALTEC.COM