

DT65E



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
DIGGER DERRICK

DT65E

Altec E-Series derricks provide a new level of performance, reliability, and safety. E-Series includes a 50 gpm variable displacement piston pump and valve technology that provides superior flow sharing to maximize jobsite efficiency and operator confidence. Servicing Altec's latest generation of derricks is easier than ever with E-Series CAN controls paired with the AXIS Service Interface. Advanced features like digger shift gearbox protection, HOP ramping, and point-of-use station select help to protect both the equipment and operators from common worksite hazards.

FEATURES

- Multi-Lever Control Station Riding Seat with Boom Side Entry
- 360° of Ingress and Egress to the Riding Seat
- Five Function Hydraulic Overload Protection System (HOP) with Ramping
- Altec RotaFloat®
- E-Series Indicator Panel
- Digger Gearbox Shift Protection
- Proportional Hydraulic Pole Guides with Interlocks
- Standard/Low Speed Selector
- Push Button Outrigger Controls with Engine Start/Stop
- Engine Start/Stop at all Control Stations
- Insulating Fiberglass Third Stage, Rated to 46kV and Below
- 15,000 lb Planetary Turntable Winch with Rope Guides
- Hydraulic Side Load Protection
- 15,000 ft-lbs Digger Motor, Two Speed Hydrasync
- Two Sets of Radial Outriggers
- Dedicated Push-Button Digger Shake
- Altec Insights, 12-months Access

OPTIONS

- Altec Opti-View® Riding Seat
- Outrigger Deploying Ladder
- Radio Remote Derrick Controls with HOP Indication
- Docking Station for Radio Upper Controls
- Material Handling Fiberglass Jib, 10 ft or 15 ft Length
- Personnel Handling Fiberglass Jib with Fiberglass Platform, 10 ft Length
- 20,000 ft-lbs Digger Motor, Two Speed Hydrasync
- Altec Insights, Lifetime Access

Recommended equipment and additional accessories, available through Altec Supply includes, the AXIS Service Interface Kit, a 5 pound fire extinguisher, triangular reflectors/road flares, fall protection equipment, outrigger pads and 2 inch front/rear receiver hitches.

SPECIFICATIONS	Rating Classification: 10 ft radius	21,051 lb (9,548 kg)
	Maximum Lift Capacity	30,000 lb (13,608 kg)
	Sheave Height (Both Booms Extended)	65.0 ft (19.8 m)
	Intermediate Boom Extended, Upper Boom Retracted	50.8 ft (15.4 m)
	Both Booms Retracted	35.9 ft (10.9 m)
	Horizontal Reach from Centerline of Rotation (Both Booms Extended)	56.2 ft (17.1 m)
	Intermediate Boom Extended, Upper Boom Retracted	41.8 ft (12.7 m)
	Both Fully Booms Retracted	26.8 ft (8.1m)
	Intermediate Boom Extension	15.1 ft (4.6 m)
	Upper Boom Extension	14.5 ft (4.4 m)
	Digger Radius (min - max)	26.9 ft (9.1 m) - 35.10 ft (10.7 m)
	Boom Articulation	-15 to 80°
	Rotation	Continuous planetary drive

*Based on a 40 in (1016 mm) chassis frame height.



OPTI-VIEW® CONTROL SEAT

The Altec Opti-View® Control Seat increases operator comfort and provides a full view of the work area.



AXIS INTEGRATION

The Altec AXIS Service Tool provides an easier user interface and increased functionality to troubleshoot or calibration the machine.



360° INGRESS/EGRESS

The standard full-view and 8-lever riding seats come with a full 360° access to the riding seat to provide superior ingress, egress independent of the unit slewing angle.



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2021 Altec Inc. All Rights Reserved. AIOSDT65E-0321-v2-r1



NEW EQUIPMENT SALES

800.958.2555

SALES@ALTEC.COM

ALTEC.COM