



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
DIGGER DERRICK

DT65H

Altec H-Series derricks are fully hydraulic and use pilot pressure controls. H-Series includes a 43 gpm variable displacement piston pump which reduces hydraulic heat generation, fuel consumption and chassis wear. Smooth and less fatiguing, the pilot pressure controls offer an improved experience for operators who prefer a fully hydraulic derrick. Additional features and options include five function HOP, Full View T-Handle Riding Seat, and Altec RotaFloat®.

FEATURES

- Multi-Lever Control Station Riding Seat with Boom Side Entry
- 360° of Ingress and Egress to the Riding Seat
- Five Function Hydraulic Overload Protection System (HOP)
- Altec RotaFloat®
- Proportional Hydraulic Pole Guides with Interlocks
- Insulating Fiberglass Third Stage, Rated to 46kV and Below
- 15,000 lb Planetary Turntable Winch with Rope Guides
- Hydraulic Side Load Protection
- Continuous Rotation with Planetary Gearbox
- 15,000 ft-lbs Digger Motor, Two Speed Hydrasync
- Hydraulic Auger Release
- Auger Stow Protection
- Two Sets of Hydraulic Radial Outriggers
- Dedicated Digger Shake

OPTIONS

- Full View T-Handle Riding Seat
- Material Handling Fiberglass Jib, 10 ft or 15 ft Length
- 20,000 ft-lbs Digger Motor, Two Speed Hydrasync
- Outrigger Deploying Ladder
- Engine Foot Throttle
- Hydraulic Hose Reel for Lower Tools

Recommended equipment and additional accessories, available through Altec Supply includes, the AXIS Service Interface Kit, a 5 pound fire extinguisher, triangular reflectors/road flares, fall protection equipment, outrigger pads and 2 inch front/rear receiver hitches.

SPECIFICATIONS	Rating Classification: 10 ft radius	21,051 lb (9548 kg)
	Maximum Lift Capacity	30,000 lb (13,608 kg)
	Sheave Height (Both Booms Extended)	65.0 ft (19.8 m)
	Intermediate Boom Extended, Upper Boom Retracted	50.8 ft (15.4 m)
	Both Booms Retracted	35.9 ft (10.9 m)
	Horizontal Reach from Centerline of Rotation (Both Booms Extended)	56.2 ft (17.1 m)
	Intermediate Boom Extended, Upper Boom Retracted	41.8 ft (12.7 m)
	Both Fully Booms Retracted	26.8 ft (8.1m)
	Intermediate Boom Extension	15.1 ft (4.6 m)
	Upper Boom Extension	14.5 ft (4.4 m)
	Digger Radius (min - max)	26.9 ft (9.1 m) - 35.8 ft (10.9 m)
	Boom Articulation	-15 to 80°
	Rotation	Continuous planetary drive
	*Based on a 40 in (1016 mm) chassis frame height.	



FULL-VIEW RIDING SEAT

The standard single handle riding seat comes with an open front, full-view seat that provides superior multi-functioning through the use of the "T-style" handle and best-in-class ingress, egress and boomtip visibility.



8-LEVER RIDING SEAT

The standard multi-lever riding seat comes with ingress, egress access from the front or the back.



360° INGRESS/EGRESS

The standard full-view and 8-lever riding seats come with a full 360° access to the riding seat to provide superior ingress, egress independent of the unit slewing angle.



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2021 Altec Inc. All Rights Reserved. AIOSTD65H-0321-v2-r1



NEW EQUIPMENT SALES

800.958.2555

SALES@ALTEC.COM

ALTEC.COM