



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**[®]
ARTICULATING TELESCOPIC
AERIAL DEVICE

FEATURES

- Side Reach of 45.1 ft (13.7 m)
- Fiberglass Platform
 - » 1300 lb (590 kg) Capacity 40 x 60 x 42 in (1016 x 1524 x 1067 mm)
 - » End-Mounted Rotating Platform
- Material Handling System
 - » Up to 1500 lb (680 kg) Jib Capacity in any Boom Position
 - » Hydraulically Extending and Articulating Jib
 - » 180° Horizontal Rotation of Jib Assembly (Manual)
- Automatic Hydraulic Platform Leveling
- Two Hydraulic Tool Circuits at Boom Tip
- Radial Outriggers
- Secondary Stowage System
- Outrigger Motion Alarm
- Back-Up Alarm

HIGH CAPACITY PLATFORM AND JIB MAXIMIZES PRODUCTIVITY



CATEGORY A RATING UP TO 765 kV AC



OPTIONS

- Platform Options
 - » Aluminum 2100 lb (953 kg) Capacity 36 x 70 x 42 in (914.4 x 1778 x 1067 mm)
 - » Aluminum 2100 lb (953 kg) Capacity 36 x 96 x 42 in (914.4 x 2438.4 x 1067 mm)
- Current Leakage Monitor
- Hydraulic Intensifier at Platform
- Fall Protection System
- Platform Liner
- Outrigger Pads
- Wheel Chocks

Recommended safety equipment, available through Altec Supply, include a fall protection system and wheel chocks for stationary set-ups.

SPECIFICATIONS	Ground to Bottom of Platform*	120.0 ft (36.6 m)
	Working Height*	125.0 ft (38.1 m)
	Maximum Reach At Platform Height	45.1 ft (13.7 m) 45.5 ft (13.9 m)
	Stowed Travel Height*	12.8 ft (3.9 m)
	Lower Boom Telescopic Extension	40.0 ft (12.2 m)
	Platform Capacity Fiberglass / Aluminum	1300 lb / 2100 lb (590 kg / 953 kg)
	Material Handling Capacity	1500 / 1400 / 1300 lb (680 / 635 / 589 kg)
	Maximum Combined Capacity, Platform and Material Handling	2100 lb (953 kg)
	Rotation	Continuous
	Maximum Dielectric Rating	765 kV
	Upper Boom Isolation Gap (Minimum)	18.1 ft (5.5 m)
	Upper Boom Articulation	0 to 140°
	Lower Boom Articulation	0 to 85°
*Based on 40 in (1016 mm) chassis frame height.		

For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.
© 2020 Altec Inc. All Rights Reserved. AIOSHL125-120