



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

Altec
HOTLINE INSULATOR
WASH TRAILER

HLIW-1200/1600T

FEATURES

- Base Assembly is Fabricated of Steel Channel, Full Rear to Tongue Eye, with Integral Cross members
- Single Axle, 20,000 lb (9,072 kg) Capacity, Equipped with Full Air Brakes
- Leaf Spring Suspension
- Trailer jack for Storage; Steel Fenders
- Trailer Grounding Assembly including electric rewind reel, 100 feet of ground cable and clamps
- Wash Gun Grounding System
- Lighting meets USA FMVSS
- Two (2) 425/65R22.5 Super Single 20 PLY Tires; 22.5 by 12.25 Disc Wheels
- Diesel Engine, 100 HP, Tier 4 Final
- 40 GAL (152 L) Fuel Tank
- Stainless Steel Water Tank, 304 Stainless Steel
- Four Stage, High-Pressure Centrifugal Water Pump
- Top or Bottom fill of Water Tank, with Strainer
- Quantity two (2) Hose Reel - Electric Rewind with 150 ft (45.7 m) length of 1 in (25 mm) Diameter Non-Conductive Hose
- Automatic Throttle System for Switching between One or Two Gun Operation
- Tool Storage Compartment
- Access Steps to reach Top Fill Opening
- Trailer Tongue outlet for use with an aerial device
- Quantity two (2) Hand-Held Wash Gun, Pilot Operated
- Throttle Mode Selector
- Constant Resistivity Monitor Provided in Tank
- Portable Resistivity Tester
- Automatic Low Water Alarm with Low Water Pump Shutdown Protection
- Two (2) Operator and Two (2) Maintenance/Parts Manuals
- Painted Black

OPTIONS

- Spare Wash Gun Assembly
- Spare Water Nozzle(s)
- Increased or Decreased Flow Nozzle(s)
- Additional Portable Resistivity Tester
- Extra Manuals
- Spare Tire and Wheel (shipped loose)

Recommended safety equipment, available through Altec Supply, include wheel chocks.

CONFIGURATIONS

HLIW-1200T

HLIW-1600T

SPECIFICATIONS

Trailer Chassis - Single Axle Rating	20,000 lb (9,072 kg)	
Tank Capacity	1,200 GAL (4,542 L)	1,600 GAL (6,057 L)
Operating Range with 1/4"(6.4 mm) Nozzle	44 GPM (167 LPM)	
Flow		
Pressure		
Single Wash Gun Each	800 PSI (5,515 kPa)	
Two Wash Gun Each	650 PSI (4,481 kPa)	
Overall Dimensions	96 in x 88 in x 208 in (244 cm x 224 cm x 528 cm)	

*Based on 40 in (1016 mm) chassis

WATER TANK BOTTOM FILL CONNECTIONS



WATER HOSE REEL WITH ELECTRIC REWIND



PORTABLE RESISTIVITY MONITOR



REAR STORAGE AND TANK TOP FILL ACCESS



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission. © 2018 Altec Inc. All Rights Reserved. AIOHLIWT SERIES-0718-v1



NEW EQUIPMENT SALES | 800.958.2555 | SALES@ALTEC.COM | ALTEC.COM