



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
ARTICULATING TELESCOPIC
AERIAL DEVICE

TA40

FEATURES

- Insulating Aerial Device
- Compensating Articulating Arm Maximizes Reach and Height Capability
- Platform Access From the Ground – With Articulating Arm Elevated or Stowed
- Side Reach up to 29.5 ft (9.0 m)
- No Counterweight or Outriggers Required for Stability
- Single Handle Multiple Function Control
- Centrifugally Cast Fiberglass Upper Boom
- Hydraulically Extended Boom
- Continuous Rotation
- Platform, 24 x 30 x 42 in (610 x 762 x 1067 mm)
- Closed Center Hydraulic System
- Hydraulic Tool Circuit at Boom Tip

OPTIONS

- Secondary Stowage System, 12 VDC
- Engine Start/Stop: Captive Air
- Lifting Eye on Lower Boom
- Outriggers, Modified A-Frame, 130 in (3302 mm) Spread
- Platform Rotator, 180°
- Reservoir, Hydraulic – 16 Gallon or 25 Gallon
- Throttle Control
- Tool Circuit at Tailshelf

Recommended safety equipment, available through Altec Supply, include a platform liner, fall protection system, wheel chocks and outrigger pads.



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission. © 2018 Altec Inc. All Rights Reserved. AITA40-418-v1

SPECIFICATIONS	Ground to Bottom of Platform*	
	End-Mount	41.0 ft (12.5 m)
	@ Reach from Centerline	11.0 ft (3.3 m)
	Working Height*	
	End-Mount	46.0 ft (14.0 m)
	Maximum Reach:	
	End-Mount	29.5 ft (9.0 m)
	@ Platform Height	17.4 ft (5.3 m)
	Stowed Travel Height*	11.9 ft (3.6 m)
	Platform Capacity	400 lb. (181 kg)
	Articulating Arm	-5° to +91°
	Boom Compensation	-38° to +75°
	Rotation	Continuous
	* Based on a 40 in (1016 mm) chassis frame height	



REACH DIAGRAM

