



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
BULLWHEEL TENSIONER

FEATURES

- Full operator's station with protective screen and adjustable seat
- All controls of machine are centrally located at operator station
- Twin five grooved 36 inch diameter bullwheels with replaceable urethane lining segments
- Adjustable three roller fairlead to allow tensioning of right hand and left hand lay conductor
- Two 24 inch diameter non-rust bronze disc bullwheel brakes
- 16 inch non-rust bronze disc reel brake
- Adjustable drop-leg front and rear jacks
- Lockable storage box, 40"L x 10"W x 9"H
- DOT 4 light system, 6 pin wire connector
- Adjustable 2.5" ID pintle eye with safety chains and an emergency break-away switch

OPTIONS

- Hydraulic accessory power pack which includes a 24 HP auxiliary diesel engine with remote engine control, hydraulic capstan (7,500 inch-lb torque) and capstan levelwind
- Hydraulic Rewind Motor for retrieval of excess conductor back onto reel
- Hydraulic front jack
- Hydraulic rear jacks
- Trailer plug - 7 pin wire connector
- 10" draw bar extension
- Roof Package
- Go Light

SPECIFICATIONS

Max Tensioning Capacity	3,000 lbs
Max Line Speed	4.5 mph
Bullwheel Diameter	36 in
Replaceable Lining Segments	Urethane castings with 5 grooves
Groove Diameter	1.5 in
Braking System	Hand wheel adjustable brake controls
Bronze Bullwheel Brakes	24 in diameter on each bullwheel
Bronze Reel Brake	16 in diameter
Max Reel Diameter	84 in
Max Reel Diameter for Capstan Equipped Configuration	80 in
Max Reel Width	51 in
Max Reel Weight	8,000 lbs
Arbor Bar Diameter	2.625 in
Overall Length	18 ft 5 in
Max Width	8 ft
Travel Height	8 ft 9 in
Min Ground Clearance	15.5 in
GVWR	15,200 lbs
Base Trailer/Machine Weight	5,600 lbs
Axle Type	Tandem, Single Tire
Axle Capacity	8,000 lbs per axle
Brakes	Electric
Tires	(4) 215/75/R17.5
Tow Hitch	2.5 inch diameter tow ring
Front jack	Manual drop down
Rear jacks	(2) Manual drop down, each side

Additional accessories available through Altec Supply including pulling grips, swivels, pilot line systems, and running grounds.

FULLY ADJUSTABLE SEAT AND CENTRALIZED CONTROLS OFFER OPERATOR COMFORT AND SAFETY



NO TOOLS REQUIRED FOR INSTALLATION AND REMOVAL OF ARBOR BAR



OPTIONAL ROOF PACKAGE



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission. © 2025 Altec Inc. All Rights Reserved. AIOSTS336-BW-723-v1

